

Soffit Application

SR/STP

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M ² /Plt	Weight (per product piece)
SR/STP/056/MAG6/SP06	Safe-R Soffit Plus 2400x1200x56 (Mag 6)	Straight	56	20	57.60	2	115.20	23.00
SR/STP/066/MAG6/SP06	Safe-R Soffit Plus 2400x1200x66 (Mag 6)	Straight	66	18	51.84	2	103.68	24.00
SR/STP/081/MAG6/SP06	Safe-R Soffit Plus 2400x1200x81 (Mag 6)	Straight	81	15	43.20	2	86.40	26.00
SR/STP/086/MAG6/SP06	Safe-R Soffit Plus 2400x1200x86 (Mag 6)	Straight	86	12	34.56	2	69.12	27.00
SR/STP/106/MAG6/SP06	Safe-R Soffit Plus 2400x1200x106 (Mag 6)	Straight	106	10	28.80	2	57.60	28.00

*Weight (rounded up to the nearest kg)

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details. All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load



Unilin Insulation UK Ltd Park Road, Holmewood, Chesterfield Derbyshire, United Kingdom, S42 5UY

t. + 44 (0) 371 222 1033 **e.** info.ui@unilin.com

unilininsulation.co.uk