

DECLARATION OF PERFORMANCE



XT/TL-MF

1. Product Type

Unique identification code of the product type:

Thin-R Thermal Liner Mech Fix

2. Type

Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Batch No on board

3. Intended Use

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal Insulation for Buildings

4. Name, Registered Trade Name

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Unilin Insulation UK Ltd Park Road, Holmewood Chesterfield, Derbyshire United Kingdom S42 5UY

5. Contact Address

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable (see 4)

6. AVCP

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

7. Notified Body (hEN)

In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

EN 13950: 2014 Notified Body: BBA/Crepim Notified Body No: 0836/2137 Performed type testing under system 3 and issued test reports.

8. Notified Body (ETA)

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Not applicable (see 7)

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T +44 (0) 371 222 1033

F +44 (0) 371 222 1044

E info.ui@unilin.com



DECLARATION OF PERFORMANCE

9. Declared Performance

| Essential Characteristics | Performance | Test Standard | Harmonised Standard |
|---------------------------|--|---------------|---------------------|
| Thermal Conductivity | 0.022 (insulation only) | EN 12667 | EN 13950: 2014 |
| Reaction to Fire | Euroclass B s1 d0 | EN 13501 | |
| Flexural Strength | ≥160N Transverse ≥400N Longitudinal | | |

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Barry Rafferty, Managing Director Unilin Insulation UK Ltd. 01-01-2023

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T +44 (0) 371 222 1033 **F** +44 (0) 371 222 1044

E info.ui@unilin.com