

SPECIFICATION CLAUSE

FLAT ROOF TOTAL FLAT ROOF SOLUTIONS

Single Ply Mechanically Fixed Systems

TR/ALU

The tapered roof insulation shall be Unilin Insulation Thin-R TR-ALU manufactured to EN 13165 by Unilin Insulation, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings. The TR-ALU_ _ _mm with a Agrément declared Lambda value of 0.022 W/mK to achieve a U-Value of _ _ _W/m²K for the roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause J42 420, J42 10.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BBA Certification No. 11/4817
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Thin-R TR-ALU Tapered Roof Insulation

Face Size

1200mm x 1200mm

Other tapers available dependent on quantity & lead time.

Edge Profile

Straight Edge

Thickness

30-50mm / 50-70mm / 70-90mm / 90-110mm