

SPECIFICATION CLAUSE

FLAT ROOF TOTAL FLAT ROOF SOLUTIONS

Partially Bonded, Self Adhered Built-up Bituminous Felt Systems XO/XD

The flat roof insulation shall be Unilin Insulation XtroDeck XO/XD ___mm thick manufactured to EN 13165:2012+A2:2016 by Unilin Insulation comprising of a rigid Polyisocyanurate (PIR) core between textured foil facings with a declared Lambda of 0.021 W/mK. The flat roof insulation shall be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause J41 420, J41 10, J41 430, J42 430. Uniclass 25 71 63 66.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165:2012+A2:2016

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire,
UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan,
Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation XtroDeck XO/XD Flat Roof Insulation

Face Size

2400mm x 1200mm

Edge Profile

Square Edge

Thickness

50mm / 60mm / 70mm / 80mm / 90mm / 100mm /
110mm / 120mm / 130mm / 140mm