



SPECIFICATION CLAUSE

XPS EXTRUDED POLYSTYRENE
INSULATION

Solid Ground Floors

XPS 300

The insulation shall be Unilin Insulation XPS 300 manufactured to EN 13164 by Soprema, comprising of High Performance Extruded Polystyrene. The Unilin Insulation XPS 300 __ _mm with declared Lambda value as low as 0.033 W/mK is to achieve a U-Value of __ _W/m²K for the floor element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause E20 200, E20 30.

Insulation

Extruded Polystyrene

Standard

BS EN 13164

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
-

Supplier

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire,
UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan,
Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Manufacturer

SOPREMA

14 rue de Saint-Nazaire, CS 60121,
67025 Strasbourg Cedex, France

E info@soprema.ie

www.soprema.ie/en

Product Reference

Unilin Insulation XPS SL Under Floor Insulation

Face Size

1250 x 600mm

Edge Profile

Rebated Edge

Thickness

30 mm / 40 mm / 50 mm / 60 mm / 80mm
/ 100mm / 120mm / 140mm / 160mm

Other sizes available dependent on quantity & lead time.