

SR/PR

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M ² /PK	Pks/Plt	M ² /Plt	Weight (per product piece)
SR/PR/025/BD/SP06	Safe-R Pitched Roof 2400x1200x25	Straight	25	12	34.56	8	276.48	3.00
SR/PR/040/BD/SP06	Safe-R Pitched Roof 2400x1200x40	Straight	40	7	20.16	8	161.28	4.00
SR/PR/050/BD/SP06	Safe-R Pitched Roof 2400x1200x50	Straight	50	6	17.28	8	138.24	5.00
SR/PR/060/BD/SP06	Safe-R Pitched Roof 2400x1200x60	Straight	60	5	14.40	8	115.20	6.00
SR/PR/075/BD/SP06	Safe-R Pitched Roof 2400x1200x75	Straight	75	4	11.52	8	92.16	8.00
SR/PR/080/BD/SP06	Safe-R Pitched Roof 2400x1200x80	Straight	80	4	11.52	7	80.64	9.00
SR/PR/100/BD/SP06	Safe-R Pitched Roof 2400x1200x100	Straight	100	4	11.52	6	69.12	10.00

*Weight (rounded up to the nearest kg)

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details.
All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load