

## **Drylining Walls**

## SR/TB

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M <sup>2</sup> /Plt	Weight (per product piece)
SR/TBDD/037.5/GYP12.5/SP06	SR T-Board DD 2400x1200x37.5 (PB 12.5S)	Straight	37.5	30	86.40	2	172.80	26.00
SR/TBDD/052.5/GYP12.5/SP06	SR T-Board DD 2400x1200x52.5 (PB 12.5S)	Straight	52.5	20	57.60	2	115.20	27.00
SR/TBDD/062.5/GYP12.5/SP06	SR T-Board DD 2400x1200x62.5 (PB 12.5S)	Straight	62.5	18	51.84	2	103.68	28.00
SR/TBDD/072.5/GYP12.5/SP06	SR T-Board DD 2400x1200x72.5 (PB 12.5S)	Straight	72.5	15	43.20	2	86.40	29.00
SR/TBDD/082.5/GYP12.5/SP06	SR T-Board DD 2400x1200x82.5 (PB 12.5S)	Straight	82.5	13	37.44	2	74.88	31.00

\*Weight (rounded up to the nearest kg)

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details. All prices are subject to the Company's Standard Terms and Conditions of Sale. \*Availability subject to quantity and lead time. +Full Truck Load



Unilin Insulation UK Ltd Park Road, Holmewood, Chesterfield Derbyshire, United Kingdom, S42 5UY

t. + 44 (0) 371 222 1033 e. info.ui@unilin.com

unilininsulation.co.uk