



SPECIFICATION CLAUSE

STONEWOOL NON-COMBUSTIBLE INSULATION

Ventilated Rainscreen Cladding

SW/RS

The rainscreen insulation shall be Unilin Insulation Stonewool ___mm manufactured to BS EN 13162. The Unilin Insulation Stonewool ___mm with a Declared Lambda value of 0.035 W/mK to achieve a U-Value of ___ W/m²K for the wall element. To be installed in accordance with instructions issued by the facade engineer.

Insulation

Semi rigid mineral wool slab

Standard

BS EN 13162

Certification

- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System

Supplier

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Manufacturer

Ravaber Yapı Ürünleri San. Ve Tic. A.Ş. Org. San. Böl. 20.cad. No:54 Kayseri

Product Reference

Unilin Insulation StoneWool SW/RS

Face Size

1200mm x 600mm

Edge Profile

Square Edge

Thickness

50mm / 75mm / 100mm / 125mm / 150mm

Other sizes available dependent on quantity & lead time.