



# SPECIFICATION CLAUSE

---

## ACCESSORIES CAVITY CLOSER

---

### Cavity Closer SAFE-R CLOSE-R

The cavity closer shall be Unilin Insulation Safe-R Cavity Closer comprising of a rigid Phenolic core between low emissivity foil facings manufactured to EN 13166 with a declared Lambda values as low as 0.020W/mK and mineral wool manufactured to EN 13162, with a declared Lambda value as low as 0.037 W/mK wrapped in a protective red sleeve to achieve a minimum 1-hour fire resistance tested to EN 1366/4. To be installed in accordance with instructions issued by Unilin Insulation.

---

#### Insulation

Phenolic Rigid Foam & Mineral Wool

#### Standard

BS EN 13166, BS EN 13162

#### Certification

- BS EN ISO 9001 Quality Management System
  - BS EN ISO 14001 Environmental Management System
  - ISO OHSMS 45001 Health and Safety Management System
- 

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033  
**F** 0371 222 1044  
**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000  
**F** 04690 66090  
**E** info.ui@unilin.com

unilininsulation.ie

---

#### Product Reference

Unilin Insulation Safe-R Cavity Closer

#### Face Size

200mm x 1200mm

#### Edge Profile

Square Edge

#### Thickness

100mm / 125mm / 150mm

---