



SPECIFICATION CLAUSE

CAVITYTHERM BUILT IN FULL FILL WALL INSULATION

Meter Box Panel

CT/ACC/MB

The Meter Box Panel insulation shall be CavityTherm CT/MB Meter Box Panel_ _ _mm thick, 600mm width and 1200mm depth, manufactured to EN 13165 by Unilin Insulation, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings, with a Lambda value of 0.022 W/mK, creating a preformed panel for an insulated Meter Box Panel in _ _ _mm cavity. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation CavityTherm CT/ACC/MB Meter Box Panel.