



# SPECIFICATION CLAUSE

---

## CAVITYTHERM BUILT IN FULL FILL WALL INSULATION

### Service Void Panel

**CT/ACC/VP**

The Service Void insulation shall be CavityTherm CT/ACC/VP Service Void Panel 250mm width and 450mm depth, manufactured to EN 13165 by Unilin Insulation, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings, with a Agrément declared Lambda value of 0.022 W/mK, creating a preformed panel for an insulated Service Void in \_\_ \_mm cavity. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause F30 12, F30 155.

---

#### Insulation

Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165

#### Certification

- BS EN ISO 9001 Quality Management System
  - BS EN ISO 14001 Environmental Management System
  - ISO OHSMS 45001 Health and Safety Management System
- 

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

---

#### Product Reference

Unilin Insulation CavityTherm CT/ACC/VP Service Void Insulation