

# SPECIFICATION CLAUSE

---

## SAFE-R PHENOLIC INSULATION

### Soffit Application

#### SR/ST

The soffit insulation shall be Safe-R SR/ST \_\_\_mm manufactured to EN 13166 by Unilin Insulation, comprising a rigid Phenolic core between low emissivity foil facings. The Safe-R SR/ST \_\_\_mm with Agrément declared Lambda value as low as 0.020 W/mK to achieve a U-Value of \_\_\_W/m<sup>2</sup>K for the soffit element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 42, P10 185, P10 180.

---

#### Insulation

Phenolic Rigid Foam

#### Standard

BS EN 13166

#### Certification

- BBA Certification No. 10/4803
  - BS EN ISO 9001 Quality Management System
  - BS EN ISO 14001 Environmental Management System
  - ISO OHSMS 45001 Health and Safety Management System
- 

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

---

#### Product Reference

Unilin Insulation Safe-R SR/ST Soffit Insulation

#### Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

#### Edge Profile

Rebated all four edges

#### Thickness

50mm / 60mm / 70mm / 75mm / 80mm / 100mm / 120mm