



# SPECIFICATION CLAUSE

---

## SAFE-R PHENOLIC INSULATION

### Drylining Walls Fixed with Adhesive Dabs

SR/TB

The insulated drylining wall insulation shall be Safe-R SR/TB manufactured to EN 13950 by Unilin Insulation, comprising a rigid Phenolic core between composite glass tissue/foil facings. The SR/TB\_ \_ \_mm with Lambda value as low as 0.020 W/mK (Phenolic only), bonded to 12.5mm plasterboard to EN 13950, achieving a U-Value of \_ \_ \_W/m<sup>2</sup>K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause K10 205, K10 15.

---

#### Insulation

Phenolic Rigid Foam

#### Standard

EN 13166, EN 13950

#### Certification

- BS EN ISO 9001 Quality Management System
  - BS EN ISO 14001 Environmental Management System
  - ISO OHSMS 45001 Health and Safety Management System
- 

#### Manufacturer

##### Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

**T** 0371 222 1033

**F** 0371 222 1044

**E** info.ui@unilin.com

unilininsulation.co.uk

##### Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

**T** 04690 66000

**F** 04690 66090

**E** info.ui@unilin.com

unilininsulation.ie

---

#### Product Reference

Unilin Insulation Safe-R SR/TB Thermal Liner Insulation

#### Face Size

2400mm x 1200mm

#### Edge Profile

Plasterboard – Tapered, Phenolic – Square Edge

#### Thickness

25mm / 40mm / 50mm / 60mm / 75mm / 80mm / 100mm

Other sizes available dependent on quantity & lead time.