

SPECIFICATION CLAUSE

THIN-R^{PIR} INSULATION

Drylining Walls Fixed with Adhesive Dabs

XT/TL

The insulated dry lining wall insulation shall be Thin-R XT/TL manufactured to BS EN 13950:2014 by Unilin Insulation, comprising of a rigid Polyisocyanurate (PIR) core with kraft paper facings. The Thin-R XT/TL ___mm with an Agrément declared Lambda value of 0.022 W/mK (PIR only) bonded to 12.5mm plasterboard, achieving a U-Value of ___W/m²K for the wall element. The insulated drylining plasterboard XT/TL shall be fixed with plaster dabs adhesive or proprietary system in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause K10 205, K10 15, K10 245, K10 35, K10 155, K45 45. Uniclass 25 71 63 66.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13950:2014

Certification

- BBA Certification No. 23/6997
 - BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation Thin-R XT/TL Thermal Liner Insulation

Face Size

UK: 2400mm x 1200mm

IRL: 2438mm x 1200 mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Plasterboard - Tapered, PIR - Square Edge

Thickness

UK: 25mm / 30mm / 40mm / 50mm / 60mm / 70mm

IRL: 17mm / 25mm / 38mm / 50mm / 60mm / 70mm