UNILIN INSULATION

SPECIFICATION CLAUSE

SAFE-R PHENOLIC INSULATION

Soffit Application (Soffit Plus)

SR/STP

The soffit insulation shall be Safe-R SR/STP _ _ _mm comprising of a rigid Phenolic core between composite foil facings manufactured to EN 13166:2012+A1:2015 by Unilin Insulation, bonded to 6mm building panel. The Safe-R SR/STP _ _ _mm with Agrément declared Lambda value as low as 0.021W/mK (Phenolic only) to achieve a U-Value of _ _ _W/m²K for the soffit element to be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 185. Uniclass Pr 25 71 63 59.

Insulation
Phenolic Rigid Foam

Standard
BS EN 13166:2012+A1:2015

Certification
- BBA Certification No. 23/6884
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd
Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033
F 0371 222 1044
E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd
Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000
F 04690 66090
E info.ui@unilin.com

unilininsulation.ie

Product Reference
Unilin Insulation Safe-R SR/STP Soffit Plus Insulation

Edge Profile
Square Edge

Face Size
2400mm x 1200mm

Thickness
56mm / 66mm / 76mm

Other sizes available dependent on quantity & lead time.