

SR019/MA (Framing)

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M ² /PK	Pks/Plt	M ² /Plt	Weight (per product piece)
SR019/MA/075/BD/SP06	Safe-R 019 Multiple Application 2400x1200x75	Straight	75	4	11.52	8	92.16	8.00
SR019/MA/080/BD/SP06	Safe-R 019 Multiple Application 2400x1200x80	Straight	80	4	11.52	7	80.64	9.00
SR019/MA/100/BD/SP06	Safe-R 019 Multiple Application 2400x1200x100	Straight	100	4	11.52	6	69.12	10.00
SR019/MA/110/BD/SP06	Safe-R 019 Multiple Application 2400x1200x110	Straight	110	3	8.64	7	60.48	11.00
SR019/MA/120/BD/SP06	Safe-R 019 Multiple Application 2400x1200x120	Straight	120	3	8.64	6	51.84	12.00
SR019/MA/150/BD/SP06	Safe-R 019 Multiple Application 2400x1200x150	Straight	150**	2	5.76	8	46.08	15.00

*Weight (rounded up to the nearest kg)
 **May be subject to minimum order quantity

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details.
 All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load



Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield
 Derbyshire, United Kingdom, S42 5UY

Ross-on-Wye, Over Industrial Estate, Netherton
 Road, Ross-on-Wye, United Kingdom, HR9 7QQ

t. + 44 (0) 371 222 1033
e. info.ui@unilin.com