



SPECIFICATION CLAUSE

THIN-R PLUS ENHANCED PIR INSULATION

Ground Supported & Suspended Floors

XT/HYF

The floor insulation shall be Unilin Insulation Thin-R Plus XT/HYF manufactured to EN 13165:2012+A2:2016 by Unilin Insulation, comprising of a rigid Polyisocyanurate (PIR) core between composite foil facings. The Thin-R Plus XT/HYF ___mm with an Agrément declared Lambda value of 0.021 W/mK to achieve a U-Value of ___ W/m²K for the floor element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause M10 290, M10 40, M13 260, M13 40, P10 250, P10 45. Uniclass 25 71 63 66.

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165:2012+A2:2016

Certification

- BBA Certification No. 23/6997
 - BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire,
UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Product Reference

Unilin Insulation Thin-R XT/HYF
Under Floor Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Square Edge

Thickness

75mm / 100mm / 125mm / 150mm