



SPECIFICATION CLAUSE

XTROLINER SUPERIOR PERFORMANCE PIR INSULATION

Sarking Warm Roof Construction

XO/SK (T&G)

The pitched roof Sarking insulation shall be XtroLiner XO/SK manufactured to EN 13165 by Unilin Insulation, comprising a rigid modified Polyisocyanurate (PIR) core with textured robust low emissivity foil facings and engineered T&G jointing. The XtroLiner XO/SK ___ mm with a Lambda value of 0.021 W/mK to achieve a U-Value of ___ W/m²K for the roof element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause P10 140, K11 695, K11 55.

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

- BBA Certification No. 12/4956
- BS EN ISO 9001 Quality Management System
- BS EN ISO 14001 Environmental Management System
- ISO OHSMS 45001 Health and Safety Management System

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Unilin Insulation Ireland Ltd

Liscarton Industrial Estate, Kells Road, Navan, Co. Meath, Ireland, C15 NP79

T 04690 66000

F 04690 66090

E info.ui@unilin.com

unilininsulation.ie

Product Reference

Unilin Insulation XtroLiner XO/SK Pitched Roof Sarking Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

T&G all four edges

Thickness

50mm / 75mm / 100mm / 125mm