

- 1) Unique identification code of the product-type: **SOPRA XPS SL, SOPRA XPS TR, SOPRA XPS CR, SOPRA XPS CB, SOPRA XPS AGRI, XPS SL, XPS TR, XPS CR, XPS CB, XPS AGRI**
- 2) Intended use/es: **Thermal insulation products for buildings**
- 3) Manufacturer: **SOPREMA - 14 rue de Saint-Nazaire, CS 60121, 67025 Strasbourg Cedex, France**
- 4) Authorised representative:
- 5) System/s of AVCP: **3**
- 6) Harmonised standard: **EN 13164:2012+A1:2015**
Notified body/ies: **1168 ; 1169 ; 1722 ; 0751 ; 0071 ; 0370 ; 1136 ; 1640**
- 7) Declared performance/s:

Essential characteristics (e)		Test Standard	Performance			Harmonised standard	
Thermal resistance - R_D	Thermal resistance - R_D and Thermal conductivity - λ_D	EN 12667	λ_D W/(m.K) 0,033 0,034 0,035 0,036	d_N mm 20-80 85-120 130-200 210-300	R_D m ² .K/W 0,60-2,40 2,50-3,55 3,70-5,70 5,80-8,30	EN 13164:2012+A1:2015	
	Thickness - d_N	EN 823	T1				
	Reaction to fire	Reaction to fire	EN 13501-1	E			
	Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (a)	EN 13501-1	E			
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance - R_D and thermal conductivity - λ_D	EN 12667	λ_D W/(m.K) 0,033 0,034 0,035 0,036	d_N mm 20-80 85-120 130-200 210-300	R_D m ² .K/W 0,60-2,40 2,50-3,55 3,70-5,70 5,80-8,30		
	Durability characteristics (b)	EN 1604	DS(70,90) (30-300 mm)				
	Freeze-thaw resistance	EN 12091	FTCD1 (30-300 mm)				
Compressive strength	Compressive stress or compressive strength (c)	EN 826	CS(10\Y)250 (20 mm) CS(10\Y)300 (30-300 mm)				
Tensile/Flexural strength	Tensile strength perpendicular to faces	EN 1607	TR200 (30-300 mm)				
Durability of compressive strength against ageing/degradation	Compressive creep	EN 1606	CC(2/1,5/50)130 (60-120 mm)				
Water permeability	Long term water absorption by total immersion	EN 12087	WL(T)0,7 (30-300 mm)				
	Long term water absorption by diffusion	EN 12088	WD(V)3 (30-55 mm)				
			WD(V)2 (60-95 mm) WD(V)1 (100-300 mm)				
Water vapour permeability	Water vapour transmission	EN 12086	MU150 (30-300 mm)				
Release of dangerous substances to the indoor environment	Release of dangerous substances (d)	---	NPD				
Continuous glowing combustion	Continuous glowing combustion (d)	---	NPD				

NPD = No performance determined

(a) The fire performance of XPS does not deteriorate with time.

(b) For dimensional stability thickness only.

(c) This characteristic also covers handling and installation.

(d) European test methods are under development.

(e) Also valid and applicable for multilayers.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Imma HUERTAS, XPS Europe Production Director**
at: **Tarragona**
on: **27.02.2023**

