

Extruded Polystyrene Insulation

XPS500

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M ² /Plt	Weight (per product piece)
XPS 30 600 1250 - 500 KPA	XPS 500kPa 1250x600x30	Ship Lap	30	14	10.50	12	126.00	1.00
XPS 40 600 1250 - 500 KPA	XPS 500kPa 1250x600x40	Ship Lap	40	10	7.50	12	90.00	1.00
XPS 50 600 1250 - 500 KPA	XPS 500kPa 1250x600x50	Ship Lap	50	8	6.00	12	72.00	2.00
XPS 60 600 1250 - 500 KPA	XPS 500kPa 1250x600x60	Ship Lap	60	7	5.25	12	63.00	2.00
XPS 80 600 1250 - 500 KPA	XPS 500kPa 1250x600x80	Ship Lap	80	5	3.75	12	45.00	2.00
XPS 100 600 1250 - 500 KPA	XPS 500kPa 1250x600x100	Ship Lap	100	4	3.00	12	36.00	3.00
XPS 120 600 1250 - 500 KPA	XPS 500kPa 1250x600x120	Ship Lap	120	3	2.25	14	31.50	4.00

*Weight (rounded up to the nearest kg)

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details. All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load



Unilin Insulation Ireland Ltd Liscarton Industrial Estate, Kells Road Navan, Co. Meath, Ireland, C15 NP79

t. +353 (0)46 906 6000 e. info.ui@unilin.com

unilininsulation.ie