STONEWOOL NON-COMBUSTIBLE INSULATION

Insulation for Ventilated Rainscreen Cladding

SW/RS

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M²/Plt	Weight (per product piece)
STW 50 600 1200 KG120	StoneWool 120kg/m3 1200x600x50	Straight	50	4	2.88	20	57.60	4.00
STW 75 600 1200 KG120	StoneWool 120kg/m3 1200x600x75	Straight	75	3	2.16	20	43.20	6.00
STW 100 600 1200 KG120	StoneWool 120kg/m3 1200x600x100	Straight	100	2	1.44	16	23.04	9.00
STW 125 600 1200 KG120	StoneWool 120kg/m3 1200x600x125	Straight	125	2	1.44	20	28.80	11.00
STW 150 600 1200 KG120	StoneWool 120kg/m3 1200x600x150	Straight	150	2	1.44	16	23.04	13.00

*Weight (rounded up to the nearest kg)

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details. All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load



Unilin Insulation UK Ltd Park Road, Holmewood, Chesterfield Derbyshire, United Kingdom, S42 5UY

t. + 44 (0) 371 222 1033 **e.** info.ui@unilin.com

unilininsulation.co.uk