TR/ALU

Material Code	Sales Text	Profile	Thickness (mm)	Shts/Pack	M²/PK	Pks/Plt	M²/Plt	Weight (per product piece)
TR/ALU/030-050/BD/SP04	Tapered ALU Board 1200x1200x30-50	Straight	40	6	8.64	10	86.40	2.00
TR/ALU/050-070/BD/SP04	Tapered ALU Board 1200x1200x50-70	Straight	60	4	5.76	10	57.60	3.00
TR/ALU/070-090/BD/SP04	Tapered ALU Board 1200x1200x70-90	Straight	80	4	5.76	8	46.08	4.00
TR/ALU/090-110/BD/SP04	Tapered ALU Board 1200x1200x90-110	Straight	100	4	5.76	6	34.56	5.00

*Weight (rounded up to the nearest kg)

Other thicknesses may be available subject to minimum order quantity and extended lead times, please contact your Area Sales Manager for further details.
All prices are subject to the Company's Standard Terms and Conditions of Sale. *Availability subject to quantity and lead time. +Full Truck Load

UNILIN INSULATION

Unilin Insulation UK Ltd
Park Road, Holmewood, Chesterfield
Derbyshire, United Kingdom, S42 5UY

Ross-on-Wye, Over Industrial Estate, Netherton
Road, Ross-on-Wye, United Kingdom, HR9 7QQ

t. + 44 (0) 371 222 1033
e. info.ui@unilin.com

unilininsulation.co.uk