



DECLARATION OF PERFORMANCE

SAFE-R 019 PHENOLIC INSULATION

SR019/MA (Framing)

1. Product Type

Unique identification code of the product type:

SR019/MA (Framing)

2. Type

Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Batch No on board

3. Intended Use

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal Insulation for Buildings

4. Name, Registered Trade Name

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Unilin Insulation UK Ltd
Park Road, Holmewood
Chesterfield, Derbyshire
United Kingdom
S42 5UY

5. Contact Address

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)

6. AVCP

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

System 1 - Reaction to Fire
System 3 - Other Characteristics

7. Approved Body

In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

EN 13166:2012+A2:2016
Approved Body: BBA
Approved Body No.: 0836
Performed type testing under system 3 and issued test reports

8. Technical Assessment Body (UKTA)

In case of the declaration of performance concerning a construction product for which a UK Technical Assessment (UKTA) has been issued:

Not relevant (see 7)

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield,
Derbyshire, UK, S42 5UY

T +44 (0) 371 222 1033

F +44 (0) 371 222 1044

E info.ui@unilin.com



DECLARATION OF PERFORMANCE

9. Declared Performance

Essential Characteristics	Performance	Test Standard	Harmonised Standard	
Thermal Conductivity	0.019	EN 12667	EN 13166:2012 +A2:2016	
Reaction to Fire	Euroclass C s2 d0	EN 13501		
Thickness	T2	EN 823		
Length & Width	Dimensions	Length		Width
	< 1250	± 5,0		± 3,0
	1250 to 2000	± 7,5		± 7,5
	2001 to 4000	± 10,0		± 7,5
> 4000	± 15,0	± 10,0		
Squareness	$S_b \leq 5\text{mm/m}$ $S_d \leq 2\text{mm/m}$	EN 824		
Flatness	Nominal thickness mm	Tolerances mm		EN 825
	< 50	$\leq 10,0$		
	50 to 100	$\leq 7,5$		
> 100	$\leq 5,0$			
Dimensional Stability	DS (70,90)	EN 1604		
Dimensional Stability	DS (N)	EN 1603		
Compressive Strength	CS (10\Y) 100	EN 826		

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Aidan Doyle, General Manager
Unilin Insulation UK Ltd.
01-01-2026

Unilin Insulation UK Ltd
Park Road, Holmewood, Chesterfield,
Derbyshire, UK, S42 5UY

T +44 (0) 371 222 1033
F +44 (0) 371 222 1044
E info.ui@unilin.com