



SPECIFICATION CLAUSE

SAFE-R 019 PHENOLIC INSULATION

Steel & Timber Frame

SR019/MA (Framing)

The wall insulation shall be Safe-R 019 MA (Framing) manufactured to EN 13166:2012+A1:2015 by Unilin Insulation, comprising of a rigid Phenolic core between composite foil facings. The Safe-R 019 MA (Framing) ___ mm with with a declared Lambda value of 0.019W/mK to achieve a U-Value of ___ W/m²K for the wall element. To be installed in accordance with instructions issued by Unilin Insulation.

Refer to NBS clause H92 776, H20 150. Uniclass Pr 25 71 63 59.

Insulation

Phenolic Rigid Foam

Standard

BS EN 13166:2012+A1:2015

Certification

- BS EN ISO 9001 Quality Management System
 - BS EN ISO 14001 Environmental Management System
 - ISO OHSMS 45001 Health and Safety Management System
-

Manufacturer

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield, Derbyshire, UK, S42 5UY

T 0371 222 1033

F 0371 222 1044

E info.ui@unilin.com

unilininsulation.co.uk

Product Reference

Unilin Insulation Safe-R 019 MA (Framing) Steel & Timber Frame Insulation

Face Size

2400mm x 1200mm

Other sizes available dependent on quantity & lead time.

Edge Profile

Square Edge

Thickness

75mm / 80mm / 100mm / 120mm